



SPECIFICATIONS

WIDTH	136'2"
LENGTH	200'
HEIGHT TO GRID	38'4"
TOTAL SQUARE FOOTAGE	27,200
ELEPHANT DOORS	North Int. 60'11"W×27'9"H to Stg. 11 South Int. 68'1"W×39'4"H to Stg. 15 Northeast 12'W×18'4"H to Spine Southeast 11'11"W×18'4"H to Spine
FLOOR TYPE	Wood Raised Foundation
FLOOR WEIGHT LIMIT	15,000 lbs
OPENS TO STAGES	11 & 15
ELEVATION CHANGE OF 34 ½" FROM STAGE 14 TO 15	

ELECTRIC SERVICES

UP TO 6 CANS OF SHOOT POWER – EACH CAN IS 2,400 AMP / 3 PHASE / 208 VOLTS	14,400 Amps Available
50A OUTLETS 208V SINGLE PHASE	1
90A 3PH MELTRIC POWER OUTLETS (208V)	3
HOUSE POWER / 20A RECEPTACLES (120V SINGLE PHASE)	50

SUPPORT SPACE

AVAILABLE IN ADJACENT BUILDING

HVAC

×10 20 TON PORTABLE COOLING UNIT	200 Tons Available
CHILLED WATER CAPACITY	Up to 40 Tons Per Header
REDLIGHT & BELL SYSTEM	Available
VENTILATION	Exhaust Fans Upon Request
HEATING	Stage Heater Upon Request

EXTRAS

TRAILER HOOKUPS	Available Upon Request
GAS CONNECTIONS	Available
COMPRESSED AIR	Available
WIRELESS INTERNET	Available Upon Request
HAZMAT SERVICES	Available Upon Request